

# CBR124



VIBRATION ANALYSIS HARDWARE

Low Smoke Zero Halogen Cable, Twisted, Shielded Pair Cable,  
Brown LSZH Jacket, 0.25 in. (6.4 mm) OD, 221 °F (105 °C) Max Temp,  
1000 ft. Reel with Blunt Cut Cable Terminations



## Specifications

|                    |                                    |
|--------------------|------------------------------------|
| Jacket Material    | Brown, Low Smoke Zero Halogen,     |
| Application        | Permanent Monitoring               |
| Conductor Quantity | 2 Conductor                        |
| Shielding Method   | Braided Shield with Drain Wire     |
| Max. Temperature   | 221 °F (105 °C)                    |
| Temperature Range  | -22 °F (-30 °C) to 221 °F (105 °C) |
| Cable Diameter     | .250 in. (6,4 mm)                  |
| Wire Gauge         | AWG = 20                           |
| Capacitance        | 49 pF/FT (nom) Conductor to Shield |
| Voltage Rating     | 1000 VDC                           |

## Ratings & Certifications



RoHS

1000 ft. Reel of Cable

Built to Order

Backed by our Unconditional Lifetime Warranty

[www.ctconline.com](http://www.ctconline.com) | [sales@ctconline.com](mailto:sales@ctconline.com) | 585-924-5900