

# CBR191



VIBRATION ANALYSIS HARDWARE

Class I, Division 2 Approved, 3 Conductor Cable, Blue Thermoplastic Elastomer (TPE) Jacket, 0.25 in. (6.4 mm) OD, 221 °F (105 °C) Max Temp, 1000 ft. Reel with Blunt Cut Cable Terminations



## Specifications

Jacket Material	Blue Thermoplastic Elastomer (TPE) Class I, Division 2
Application	Permanent Monitoring
Conductor Quantity	3 Conductor
Shielding Method	Braided Shield with Drain Wire
Max. Temperature	221 °F (105 °C)
Temperature Range	-22 °F (-30 °C) to 221 °F (105 °C)
Cable Diameter	.250 in. (6,4 mm)
Wire Gauge	AWG = 20
Capacitance	44.13 pF/ft (nom) Conductor to Shield
Voltage Rating	1000 VDC

**C1D2 Compliant per NFPA70 guidelines when used with:**

D3Q

**Ratings & Certifications**



**RoHS**

**1000 ft. Reel of Cable**

**Built to Order**

**Backed by our Unconditional Lifetime Warranty**

[www.ctconline.com](http://www.ctconline.com) | [sales@ctconline.com](mailto:sales@ctconline.com) | 585-924-5900