

- For the intrinsically safe operation of a wide range of devices, such as HART transmitters, solenoid valves, sensors, zero-potential contacts and many more
- Compact, space-saving devices that are easy to install on a DIN rail
- Quick to install as barriers can be simultaneously snapped onto rail and connected to PE

WebCode 9002A



The 9002 series INTRINSPAK two-channel safety barriers enable the intrinsically safe operation of virtually all field devices. The comprehensive portfolio and the combination of safety barriers cover a wide variety of signals. The devices are incredibly robust and require very little space. The back-up fuse is a convenient feature as it is standardised for all variants.

Technical Data

Explosion Protection

Application range (zones)	2 22
Ex interface zone	0 1 2 20 21 22
Certificate IECEX Gas	IECEX PTB 08.0057X
Certificate ATEX Gas	PTB 01 ATEX 2053 X
Certificate IECEX Dust	IECEX PTB 08.0057X
Certificate ATEX Dust	PTB 01 ATEX 2053 X
Gas explosion protection IECEX	Ex nA [ja Ga] IIC/IIB T4 Gc
Gas explosion protection ATEX	⊕ II 3 (1) G Ex nA [ja Ga] IIC/IIB T4 Gc
Dust explosion protection IECEX	[Ex ia Da] IIIC
Dust explosion protection ATEX	⊕ II (1) D [Ex ia Da] IIIC
Certificates	ATEX (PTB), Brazil (ULB), Canada (CSA), China (CQST), EAC (STV), IECEX (PTB), Korea (KGS), USA (FM), USA (UL)
EAC certificate	TS RU S-DE.GB04.B.00134
Installation	in Zone 2, Division 2 and in safe area

Safety Data

Max. voltage U_o	28 V
Max. voltage U_o	28 V 28 V 28 V
Max. current I_o	90 mA
Max. power P_o	630 mW
Max. permissible external capacitance C_o for IIC	0.083 μ F

9002/13-280-093-001 Art. No. 158852

Safety Data

Max. permissible external capacitance C_o for IIB	0.65 μ F
Max. permissible external inductance L_o for IIC	2.2 mH
Max. permissible external inductance L_o for IIB	14 mH
Further information	see respective certificate and operating instructions

Electrical Data

Number of channels	2
Channel	1 2 1 + 2
Nominal voltage U_N	24 V 24 V
Min. resistance R_{min}	321 Ω
Max. resistance R_{max}	358 Ω
Max. current I_o	90 mA 3 mA 93 mA
Max. power P_o	630 mW 21 mW 651 mW
DC rated operational voltage	24 V
Power supply	Controlled, nominal voltage
Nominal voltage	24 V
Maximum resistance R_{max}	358 Ω
Minimum resistance R_{min}	321 Ω
Maximum output current I_{max}	67 mA
Potential	Pos. poten. w/diode
Potential Ch 1	Positive potential
Potential Ch 2	Evaluation barrier +potential
Ohm.curr.lim.usingfreq. \geq 50mA	\leq 100 kHz
Ohm.curr.lim.usingfreq. \leq 50 mA	\leq 50 kHz
leak leakage current for U_N	\leq 2 μ A
leak leakage current for U_N 2	(Unless specified otherwise)

Channel	Nominal voltage U_N	Min. resistance R_{min}	Max. resistance R_{max}	Max. voltage U_o	Max. current I_o	Max. power P_o
1	24.00 V	321.00 Ω	358.00 Ω	28.00 V	90.0 mA	630.000 mW
2	24.00 V			28.00 V	3.0 mA	21.000 mW
1 + 2				28.00 V	93.0 mA	651.000 mW

Ambient Conditions

Min. ambient temperature	-20 $^{\circ}$ C
--------------------------	------------------

9002/13-280-093-001 Art. No. 158852

Ambient Conditions

Max. ambient temperature	+60 °C
Ambient temperature	-20 °C ... +60 °C
Min. storage temperature	-20 °C
Max. storage temperature	+75 °C
Storage temperature	-20 °C ... +75 °C
Maximum relative humidity	95% on av., no condensation
Temperature influence	≤ 0,25 %/10K



Mechanical Data

Degree of protection (IP)	IP40
Degree of protection (IP) Terminals	IP20
Enclosure material	Polyamide 6GF
Number of connection terminals	4
Max. clamping range	1.5 mm ²
Connection cross-section	4 mm ²
Type of connection cable	Finely stranded Solid
Width	103 mm
Length	12 mm
Mounting depth	72 mm
Weight	0.11 kg

Mounting / Installation

Connection type	2 PA
-----------------	------



Technical Drawings



Picture F

Two-channel safety barriers, safety barrier potential: + / evaluation barrier potential: +

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations





Mounting on DIN rail NS 35/15

Safety Barriers

Dual-channel safety barrier









9002/13-280-093-001 Art. No. 158852



Mounting on mounting plate by means of adaptor

Mounting on DIN rail NS 32 by means of adaptor and mounting attachment, moulded plastic

Accessories and Spare Parts

		Art. No.
Back-up fuse		
	For all safety barriers Series 9001, 9002 and 9004 unit: 5 pcs.	158964
Holder for label		Art. No.
	Transparent cover for labelling	158977
Labelling paper		Art. No.
	Perforated, for typing Format: DIN A4 Packaging unit: 80 pieces	158973
Adaptor		Art. No.
	Adaptor allows installation of a safety barrier Series 900x on a mounting plate of a previous series.	158826
Mounting attachment moulded plastic		Art. No.
	Enables mounting of safety barrier on a G-rail.	165283
DIN rail		Art. No.
	NS35/15 (meter length)	103714

Safety Barriers


Dual-channel safety barrier



9002/13-280-093-001 Art. No. 158852

Earth terminal

Art. No.



USLKG 5 (wire range 4 mm²)
Terminal enables connection of protective conductors to DIN rail. Colour green-yellow.

112760

USLKG 6 N (wire range 6 mm²)
Terminal enables connection of protective / earthing conductors to DIN rail. Colour green-yellow.

112599

Fuse holder

Art. No.



Fuse holder is snapped onto the side of the safety barrier and can be equipped with up to 5 back-up fuses (replacement).

158834




Insulating stand off

Art. No.



Suitable for DIN rail NS35/15, allows electrically insulated mounting of DIN rail from mounting plate.

158828



We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.