

# MEB210 Series



Lightweight, Cost Effective Molded Sensor, Top Exit Molded Integral Cable, 10-32 Mounting, 100 mV/g, ±10%

VIBRATION ANALYSIS HARDWARE




## Product Features

- ▶ Nylon Overmolded Accelerometer
- ▶ IP68 Rated
- ▶ To mount utilizing an adhesive mounting pad, CTC recommends purchasing MH108-3B (1/4-28-32 Adapter Stud) with MH130-4A (0.75" OD Mounting Disk with 1/4-28 Blind Tapped Hole)

### MEB210

CB127 Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common



Stock Product

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	MEB210	M/MEB210	<b>Environmental</b>		
Sensitivity (±10%)		100 mV/g	Operating Temperature Range	-58 to 250°F	-50 to 121°C
Frequency Response (±3dB)	30-900,000 CPM	0.5 Hz-15 kHz	Maximum Shock Protection		10,000 g, peak
Frequency Response (±10%)	60-600,000 CPM	1 Hz-10 kHz	Electromagnetic Sensitivity		CE Approved
Dynamic Range		± 80g, peak *Vsource ≥ 22V, 12Vbias	Sealing		IP68 Integrally Molded Cable
<b>Electrical</b>			Submersible Depth	200 ft.	61 m
Settling Time		< 2 Seconds	SIL Rating		SIL 2
Voltage Source (IEPE)		18-30 VDC	<b>Physical</b>		
Constant Current Excitation		2-10 mA	Sensing Element		PZT Ceramic
Spectral Noise @ 10 Hz		30 µg/√Hz	Sensing Structure		Shear Mode
Spectral Noise @ 100 Hz		4 µg/√Hz	Weight	0.35 oz	10 grams
Spectral Noise @ 1000 Hz		2 µg/√Hz	Mounting Base		316L Stainless Steel
Output Impedance		< 100 ohm	Mounting Thread		10-32 UNF
Bias Output Voltage		10-14 VDC	Cable Jacket Diameter		0.14 in (3.6 mm)
Case Isolation		>10 <sup>8</sup> ohm	Cable Jacket Material		Polyurethane
			Cable Conductor		26 AWG Twisted Shielded Pair
			Resonant Frequency	2,640,000 CPM	44 kHz
			Mounting Torque	1.5 - 2.5 ft. lbs	2.0 to 3.4 Nm
			Mounting Hardware Supplied	10-32 Stud	M5 Stud
			Calibration Certificate		CA10

## Typical Frequency Response



Backed by our Unconditional Lifetime Warranty & Free Annual Recalibration Service

www.ctconline.com | sales@ctconline.com | 585-924-5900